NCR SelfServ[™] 27

Through-the-Wall Cash Dispense ATM

Connecting the World with Cash

Designed to catch the attention of your customers, the SelfServ 27 has a modern and contemporary look and feel, driving a digital-first interaction at the ATM channel. The SelfServ 27 performs brilliantly in locations where cash is in constant demand and is designed to handle the highest transaction volumes, with S2 Media Dispense Module as the engine.

Experience

Brand perception depends on the customer experience. SelfServ 27 offers your consumers a modern, digital-first experience with multi-touch display, integrated contactless card reader and dynamically adjustable media entry and exit indicators. Coupled with NCR Enterprise Software and ATM Marketing, SelfServ 27 unlocks a personalized user flow and increases ROI.

Availability

ATM uptime matters. SelfServ 27 is powered by S2 Media Dispense Module. It has market-leading cassette capacity and drives longer replenishment cycles, keeping your device online for longer. With greater FRUs and State of Health indicators, S2 helps you get your ATM back up and running faster than other devices on the market.

Security

SelfServ 27 has security built in. The combination of S2 Media Dispense Module and integrated cash exit and consumer portrait cameras protects your device against cash trap attacks and transaction reversal fraud. With the latest Skimming Protection Solution and NCR Secure, your consumers are protected against card skimming fraud too.





Key features

- Intuitive Touch Screen—High quality touchscreen with multitouch capability for swipe & gesture functionality, simulating modern consumer technology
- Media handling 2.0—driven by the market-leading S2
 Media Dispense Module, featuring up to 60 note bunch, 2-4 cassettes, 2,800* cassette capacity

Technical specifications**

Product dimensions (with CEN 1)

- HEIGHT 56.7" (1463mm)
- WIDTH 25.83" (656mm)
- DEPTH 42.87" (1089mm)
- WEIGHT (CEN 1)1135lb (515kg)

Consumer interface

- Display 15" LCD multi-touch, or FDK, optional privacy filter
- Dynamic Integrated Media Entry and Exit Indicators (MEEI)
- PIN Pad EPP (PCI compliant, polycarbonate or stainless steel)
- Card Readers EMV Ready, Tamper Resistant Smart DIP, Track 2 or Track 3 IMCRW (Motorized) with CROPF
- Contactless Integrated Reader (via card, smartphone or wearable)
- Biometric Ready
- Audio Optional high quality public audio and/or sound jack with volume control
- Barcode Reader 2D Reader supporting 1D and 2D documents

Media handling 2.0 technology

- Cash Dispense: S2 Media Dispense Module: Up to 60 note bunch,
 346mm cassette, up to 2800* notes per cassette, vacuum-based with
 adaptive pick technology, configurable purge bin capability with retract
 and single note divert, programmable carriage with built-in anti-cash
 trapping technology
- * Depending on note quality and thickness ** Regional configurations and feature availability apply

Why NCR?

NCR Corporation (NYSE: NCR) is a leading software and services-led enterprise provider in the financial, retail, hospitality, small business and telecom and technology industries. We run key aspects of our clients' business so they can focus on what they do best.

- Easy to service—Simplified parts for enhanced first line maintenance and increased number of field replaceable units for quick repairs
- Best-in-class design—for the banking consumers of the future—incorporating design cues from NCR's awardwinning SelfServ™ 80 series and delivering a modern and digital-first brand image

Operating platform

- Intel® Celeron, i3 and i5 processor options
- 4GB, 8GB or 16GB RAM, DVD-RW Drive
- Primary or Secondary Hard Disk Drive or Solid-State Drive

Software

- Windows 10
- NCR Software Suite

Security

- Cameras Integrated Cash Exit and Consumer Portrait
- Integrated flush Skimming Protection Solution UPS, UL437 Lock
 - Alarms Standard and High Security Alarm options
 - Safes CEN I, CEN III, CEN III GasEx, CEN IV, CEN IV GasEx

Printers

- Receipt 80mm 203dpi graphics thermal printer or capable of ereceipts to mobile device
- Electronic Journal

Environmental

- Internal Standard 32*F to 104*F (0*C to 40*C)
- External Standard -31*F to 122*F (-35*C to 50*C)
- Humidity (interior) 20% to 80% ; Humidity (exterior) 10% to 90%
- Acoustics 65dB (A) when idle, 68dB 75dB (A) when operating, Servicing
- 7" LCD Control Operator Panel, Rear access only

NCR is headquartered in Atlanta, GA with 34,000 employees and solutions in 141 countries. NCR is a trademark of NCR Corporation in the United States and other countries.

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

All brand and product names appearing in this document are trademarks, registered trademarks or service marks of their respective holders. © 2022 NCR Corporation Patents Pending ncr.com

